

Product Code: CMA161

Technical Specification

Luckinslive 425262397

Description: 1 Gang 2 Way 100W Dimmer Switch





Rear Housing: Nylon

Terminal Torque Value (Nm) 0.25

Frequency (Hz) 50

Terminal Screws: Steel & Yellow Passivated

General Information

Plate Dimensions (mm) 86 (W) x 86 (H) x 9.5 (D)

Plate Fixing Centres - Horizontal (mm) 603

> Style Rounded Profile Materials Front Plate: Urea

> > Terminals: Brass PCB: Mixed Components

Anti Microbial Certified

Operating Voltage (AC) 250

Load Rating (W) 5 - 100

Load Rating Comments Suitable For LED

> Termination Type Screw

Terminal Size (mm) Ø3.5

Terminal Capacity - Solid (mm²) 2 x 1.5

2 Way Switch

Switch Control Type Press - ON/OFF, Rotate - Dim

Dimmer Technology Type Trailing Edge Minimum Brightness Programming Available Minimum Back Box Depth (mm)

> **Ingress Protection** IP20 Operational Temperature (°C) -5 to +40

> > Warranty (Years) Warranty - Electronics (Years) 2

BS EN 60669-1, BS EN 60669-2-1, BS EN 55015, BS EN 61000-3-2 **Standards**

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.

We recommend the use of branded LED lamps with all Mode® trailing edge dimmers. The use of inferior, nonbranded lamps may require the nominal rating of the dimmer to be reduced. For further information please contact Click® Technical support team.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

All white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases as well as anti-viral properties against enveloped and non-enveloped viruses.

All products have been independently tested with 99.9% of enveloped viruses and 92% of non-enveloped viruses killed off whilst achieving a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.

Compatible **Dimmer Modules** MD9014: 100W Dual Mode LED Dimmer Module

MD9001: 6A Push ON/OFF (Dummy Dimmer / Non Dimmable) Module

MD9010: 1-10V Analogue Rotary Dimmer Module

Scolmore House, Mariner, Lichfield Road Industrial Estate, Tamworth, Staffordshire, B79 7UL United Kingdom **T:** +44 (0)1827 63454 | **F:** +44 (0)1827 63362 E: sales@scolmore.com | W: scolmore.com

Specification is subject to change without notice. Errors & Omissions excluded.









