

Product Code: CMA735AG

Luckinslive 402391809

Description: 13A 1 Gang Double Pole Switched Locating Plug Socket Outlet



### General Information

|                                              |                                          |                                            |
|----------------------------------------------|------------------------------------------|--------------------------------------------|
| Plate Dimensions (mm)                        | 86 (W) x 86 (H) x 9.5 (D)                |                                            |
| Plate Fixing Centres - Horizontal (mm)       | 60.3                                     |                                            |
| Style                                        | Rounded Profile                          |                                            |
| Colour                                       | Anthracite Grey                          |                                            |
| Supplied Fixing Screw Finish                 | Polished Chrome                          |                                            |
| Switch Finish                                | Polar White                              |                                            |
| Materials                                    | Front Plate & Rocker Switch: Urea        | Rear Housing: Urea                         |
|                                              | Terminals: Brass                         | Terminal Screws: Steel & Yellow Passivated |
|                                              | Contacts: Silver "on-lay" Copper / Brass | Internal Busbars: Formed Pressed Brass     |
|                                              | Earth Strap: Mild Steel                  |                                            |
| Anti Microbial Certified                     | Yes                                      |                                            |
| Operating Voltage (AC)                       | 250                                      | Frequency (Hz) 50                          |
| Resistive Load Rating (A)                    | 13                                       |                                            |
| Termination Type                             | Screw                                    |                                            |
| Terminal Size (mm)                           | Ø5                                       | Terminal Torque Value (Nm) 2               |
| Terminal Capacity - Solid (mm <sup>2</sup> ) | 3 x 2.5 or 2 x 4                         |                                            |
| Double Pole Switch                           | Yes                                      |                                            |
| Twin Earth Terminals                         | No                                       |                                            |
| Minimum Back Box Depth (mm)                  | 25                                       |                                            |
| Ingress Protection                           | IP20                                     |                                            |
| Operational Temperature (°C)                 | -5 to +40                                |                                            |
| Warranty (Years)                             | 25                                       |                                            |

**Standards** BS 1363-2

### Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

All white & grey moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases as well as anti-viral properties against enveloped and non-enveloped viruses.

All products have been independently tested with 99.9% of enveloped viruses and 92% of non-enveloped viruses killed off whilst achieving a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.

