


Product Code: VPSS535BK

Technical Specification



Description: 13A Ingot 1 Gang Double Pole Switched Socket Outlet







General Information

Plate Dimensions (mm) 88 (W) x 88 (H) x 8 (D)

Dimensions With Gasket (mm) 91 (W) x 91 (H) x 9 (D)

Plate Fixing Centres - Horizontal (mm) 60.3

> Style Victorian

Finish Stainless Steel

Insert Colour Black Gasket Colour Black

> Materials Front Plate: Stainless Steel

> > Switch Cover: Stainless Steel

Terminal Screws: Steel & Yellow Passivated

Internal Busbars: Formed Pressed Brass

Gasket: Nylon

Anti Microbial Certified

Operating Voltage (AC) 250

Termination Type Screw

Terminal Size (mm)

Ingress Protection IP20

Operational Temperature (°C) -5 to +40

Warranty (Years)

Standards BS 1363-2

Insert & Housing: Urea

Earth Strap: Mild Steel

Frequency (Hz) 50

Contacts: Silver "on-lay" Copper / Brass

Terminals: Brass

Terminal Torque Value (Nm) 2

Resistive Load Rating (A) 13

Terminal Capacity - Solid (mm²) 3 x 2.5 or 2 x 4

Double Pole Switch

Minimum Back Box Depth (mm)

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.











